

KELLY-MOORE PAINT CO INC -- ACRY-LUSTRE ACRYLIC SEMI-GLOSS, 1250-SERIES -- 8010-00N022018

===== Product Identification =====

Product ID:ACRY-LUSTRE ACRYLIC SEMI-GLOSS, 1250-SERIES

MSDS Date:12/18/1987

FSC:8010

NIIN:00N022018

MSDS Number: BLSBL

=== Responsible Party ===

Company Name:KELLY-MOORE PAINT CO INC

Address:1015 COMMERCIAL ST

City:SAN CARLOS

State:CA

ZIP:94070

Country:US

Info Phone Num:415-592-8337

Emergency Phone Num:800-424-9300(CHEMTREC)

Preparer's Name:JULIAN SCHAFER

CAGE:KELLY

=== Contractor Identification ===

Company Name:KELLY-MOORE PAINT CO INC

Address:1015 COMMERCIAL ST

City:SAN CARLOS

State:CA

ZIP:94070

Country:US

Phone:415-592-8337

CAGE:KELLY

===== Composition/Information on Ingredients =====

Ingred Name:PROPIONIC ACID, 2-METHYL-, MONOESTER

W/2,2,4-TRIMETHYL-1,3-PENTANEDIOL; (TEXANOL). VP: 0.04@68F

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: <5%

Ingred Name:HEXYLENE GLYCOL

CAS:107-41-5

RTECS #:SA0810000

Fraction by Wt: <5%

OSHA PEL:C 25 PPM

ACGIH TLV:C 25 PPM; 9192

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: DIZZINESS, HEADACHE, NAUSEA,
CONFUSION, IRRITATION TO UPPER RESPIRATORY TRACT, UNCON, SKIN AND
EYE IRRITATION. CHRONIC: NONE KNOWN.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:SEE YOUR PHYS FOR SPECIFIC MED
OPINION REGARDING YOUR CONDITION.

===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR. RESTORE BREATHING, CONSULT PHYS.
EYE: FLUSH WITH LARGE VOLUMES OF WATER FOR AT LEAST 15 MIN. GET MED
ATTN. SKIN: WIPE OFF WITH RAG. WASH THOROUGHLY WITH SOAP AND WATER.
ING EST: CONSULT HOSPITAL EMERGENCY ROOM OR POISON CONTROL CENTER
IMMED.

===== Fire Fighting Measures =====

Flash Point:>200F,>93C
Extinguishing Media:NOT APPLICABLE. MEDIA SUITABLE FOR SURROUNDING FIRE
.
Fire Fighting Procedures:NONE. WEAR NIOSH/MSHA APPROVED SCBA AND FULL
PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE (DUE TO
BUILDUP OF STEAM PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA TO PREVENT BUILDUP OF VAPORS.
FOR SMALL SPILLS, SOAK UP WITH ABSORBANT. FOR LARGE SPILLS, DIKE
AREA WITH ABSORBENT MATERIAL AND SCOOP UP LIQUIDS.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE UPRIGHT IN SEALED CONTAINERS
AWAY FROM HEAT AND FLAME.
Other Precautions:REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPRVD PARTICLE MASK TO AVOID
BRTHG SPRAY MIST OR SANDING DUST, IF LOC VENT IS ADEQ TO KEEP TLV
W/IN ACCEPTABLE LIMITS. IF LOC VENT IS NOT ADEQ, USE NIOSH/NSHA
APPRVD RESP FOR ORG VAP S UPPLIED/SCBA IS RECOMMENDED.
Ventilation:LOCAL EXHAUST SUFFICIENT TO KEEP TLV BELOW PRESCRIBED
LIMITS.
Protective Gloves:RECOMMENDED.
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
MRF TRADE NAME/PART NO: ALL COLORS.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:212F,100C
Vapor Pres:SEE INGRED
Vapor Density: